

## Sucker Rods Dimensional Range

Tenaris offers a comprehensive range of sucker rods from 5/8" to 1 1/2", in different steel grades. Check which product best meets your needs.

DIMENSIONAL RANGE				
TECHNOLOGIES	ROD BODY DIAMETER [INCH]	NOMINAL COUPLING DIAMETER [INCH]	OIL LIFTING SYSTEMS	
			CONVENTIONAL PUMPING	PROGRESSIVE CAVITY PUMPING
<b>Premium Connection Rods</b>	3/4	3/4	X	X
	7/8	7/8	X*	X*
	1	1	X	X
<b>PCPRod® X- Torque</b>	1	7/8 (modified pin)		X
	1 1/4	1 (modified pin)		X
	1 1/4	1 1/8 (modified pin)		X
	1 1/2	1 1/8 (modified pin)		X
<b>PCPRod® Hollow</b>	1.9 (PCPRod® 900)	1.9 (flush)		X
	1.9 (PCPRod® 1000)	1.9 (flush)		X
	1.66 (PCPRod® 1500)	1.97 (near-flush)		X
	1.9 (PCPRod® 2500)	2.36 (near-flush)		X
<b>High Strength Rods (Grades UHS, MMS and Plus)</b>	5/8	5/8	X	X
	3/4	3/4	X	X
	7/8	7/8	X*	X*
	1	1	X	X
	1 1/8	1 1/8	X	X
<b>API Sucker Rods (Grades C, K and D)</b>	5/8	5/8	X	X
	3/4	3/4	X	X
	7/8	7/8	X	X
	1	1	X	X
	1 1/8	1 1/8	X	X

(\*) 7/8" Premium Connection Rods, 7/8" Grade Plus Rods as well as 7/8" rods with 1" couplings in all grades have a reinforced pin with dimensions larger than API.